



**Product:** PG-5 Masking Tape – General Purpose

**Description:** A smooth crepe, pressure-sensitive masking tape. PG5 offers an excellent balance of quick stick, panel adhesion and holding properties. Recommended for most paint masking applications where excellent cornering with clean removal is desired. Will support masking paper aprons at 160° F (70°C) for 30 minutes. Not recommended for outdoor exposure.

<b>Nominal Values:</b>	Backing	Fine Structured Crepe Paper
	Adhesive	Natural Rubber/Resin
	Adhesion to Steel (oz/in of width)	33 (9 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	8 (2.2 N/25mm)
	To Steel	17 (4.6 N/25mm)
	Tensile Strength (lbs/in of width)	25 (109 N/25mm)
	Elongation (% at break)	10
	Thickness (mils)	6.3 (0.160 mm)
	Government Specification Conformance	C.I.D. A-A-883B Type 1

**Features:** Temperature resistant operating range of 50° F to 200° F. (10°C to 93°C)

**Standard Sizes:** 18mm x 54.8m, 24mm x 54.8m, 36mm x 54.8m, 48mm x 54.8m, 72mm x 54.8m

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

07/03