



PRODUCT DATA SHEET

Product: PG-505 Masking Tape - General Purpose

Description: A general grade, industrial, pressure-sensitive masking tape. PG505 offers an excellent balance of quick stick, panel adhesion and holding properties. Not recommended for outdoor exposure.

Nominal Values:	Backing	Smooth Crepe Paper
	Adhesive	Natural Rubber/Resin
	Adhesion to Steel (oz/in of width)	33 (9 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	5 (1.4 N/25mm)
	To Steel	11 (3 N/25mm)
	Tensile Strength (lbs/in of width)	20 (88 N/25mm)
	Elongation (% at break)	10
	Thickness (mils)	5.8 (0.147 mm)
	Government Specification Conformance	ASTM D6123, Type I C.I.D. A-A-883B Type 1

Features: Temperature resistant operating range of 50° F to 200° F. (10°C to 93°C)

Standard Sizes: 12mm x 54.8m, 18mm x 54.8m, 24mm x 54.8m, 36mm x 54.8m
48mm x 54.8m, 72mm x 54.8m

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

08/04