

231



POLYKEN® 231
Military Grade Duct Tape


APPLICATIONS

- Quality waterproof packaging tape for military packaging and other demanding applications.
- · General repair and sealing.

FEATURES & BENEFITS

- Waterproof.
- High adhesion sticks to a variety of surfaces.
- · Strong and durable.
- Meets Federal Specification ASTM D-5486 Type IV, Class 1 (supersedes PPP-T-60E, and PPP-T-60D).
- · Meets Defense Standard 81-25.

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated Construction Backing:

· Polyethylene Coated Cloth

Adhesive:

Rubber

Colors:

· Black, Olive Drab, Silver

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	12 mils	304.80 μ	ASTM D 1000
Adhesion to Steel	80 oz./in.	8.76 N/cm	PSTC-1
Adhesion to Backing	30 oz./in.	3.28 N/cm	PSTC-1
Tensile Strength	50 lb./in.	87.56 N/cm	ASTM D 1000
Unwind Force	40 oz./in.	4.38 N/cm	ASTM D 1000
Maximum Performance Temperature	200 F		

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical person To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warr of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



^{**}Recommended storage conditions: 40-60% Humidity, 60°F-80°F