IPG # 51588 Polyester Film Electrical Tape

Product Description: This combination of a tough, conformable polyester backing and rubber thermosetting adhesive may be used for a variety of electrical applications. This tape is abrasion and puncture resistant, resists chemicals and solvents when thermoset, and has excellent electrical insulating properties.

Applications: Coil wrapping, anchoring, harnessing, holding, insulating tabbing and interlayer insulating.

Technical Data:

Backing :	Polyester	Color:	Clear
Backing Thickness:1.0 mil		Adhesive:	Rubber Thermosetting
Total Thickness:	2.2 mil (0.056 mm)	Dielectric Strength:	5000 Volts
Temp. Class:	130°C / B	Insulation Resistan	ce:10 ⁶ megohms
Tensile Strength:	25 lbs/in (110 N/25mm)	Adhesion to Steel:	50 oz/in (13.7 N/25mm)
Elongation:	100%	Storage Stability:	Very Good
Electrolytic Corrosion	1.0 Direct/A , 1*	Solvent Resistance	: Very Good
Flammability	BU 1*	Moisture Resistance	e: Excellent
Mil Spec Approved	MIL-1-15126F Type MF-2.5	CSA File #	LR94980
UL File #	E20780		

^{*}VDE 0340

Figures shown are averages and should not be used for writing specifications. Similar test conducted on any individual sample may vary in results. Tests are conducted in accordance with ASTM D1000 where applicable.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. 03/06