Product: #519 --- Medium Grade / General Purpose Masking Tape

Description: A conformable / flexible, high quality semi-bleached crepe paper, coated with

natural / synthetic rubber pressure-sensitive adhesive capable of withstanding bake temperature up to 180°F (82°C) for up to one hour and/or exposure to ultra-violet (UV) light for up to (5) hours. #519 offers consistent conformability and tensile

strength for general purpose bundling, protecting, and various industrial

applications. Product can be qualified to meet Federal Specifications PPP-T-42C,

Type I and UU-T-106, Type I as well as C.I.D. A-A-883, Type I.

Nominal

Values: Backing Crepe Paper

Color Natural

Adhesive Natural / Synthetic Rubber

Adhesion to Steel (oz/in of width) PSTC-1 40 (11 N/25mm)

Tensile Strength (lbs/in of width) PSTC-31 18 (79 N/25mm)

Elongation (% at break) PSTC-31 7.0

Total Thickness (mils) PSTC-33 7.0 (0.178mm))

Quick Stick to Steel (oz/in of width) PSTC-5 17 (4.6 N/25mm)

Product

Application: Interior paint masking, Spray painting (air-dry) autos, boats, etc., Boat

manufacturing (fibreglass), Silk screening, mail rooms, Marble manufacturing (man-made), Golf club shaft (build-up), Carpet pad / pad splicing, Freezer tape, and

for Light Bundling, Packaging, Splicing & Tabbing.

Standard

Sizes: 1/4" x 60 yards, ½" x 60 yards, ¾" x 60 yards, 1" x 60 yards, 1-1/2" x 60 yards,

2" x 60 yards, 3" x 60 yards, and 4" x 60 yards.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. 01-08