



intertape polymer group

Product Code **PS-3**

**Product:** PS-3 Packaging Tape - Extra Strength Paper

**Description:** High Performance, water resistant, carton sealing, kraft flatback, pressure-sensitive tape featuring easy release from roll, good quick-stick, with excellent bond to carton and good edge tear. Performs well as a low temperature splicing tape. Product is not repulpable.

<b>Nominal Values:</b>	Backing	Kraft Flatback
	Adhesive	Natural Rubber/Resin
	Adhesion to Steel (oz/in of width)	70 (19.2 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	11 (3.0 N/25mm)
	To Steel	30 (8.2 N/25mm)
	Tensile Strength (lbs/in of width)	
	Machine Direction	51 (223 N/25mm)
	Cross Direction	32 (140 N/25mm)
	Elongation (% at break)	4
	Thickness (mils)	7.9 (0.20 mm)
	Specification Conformance	PPP-T-76C, Type V A-A-1830, Type 1, Class 1 A-A-884, Type 1, Class 1

**Features:** Temperature resistant operating range of 40° F to 250° F. (4°C to 120C°)

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

08/03

3647 Cortez Road West, Suite 102 • Bradenton, Florida, U.S.A. 34210

©Copyright, 1999 Intertape Polymer Group

PRODUCT DATA SHEET