



intertape polymer group

Product Code **RG-3**

Product: **RG-3 Filament Tape - Uni-Directional Fiberglass Reinforced**

Description: A fiberglass reinforced, polyester backed, pressure-sensitive strapping tape with medium strength and good adhesion. Designed for the majority of packaging, palletizing and utilizing applications where the performance and versatility of natural rubber/resin adhesive is desired.

Nominal Values:	Backing	57 ga Polyester
	Adhesive	Natural Rubber/Resin
	Reinforcement	Fiberglass
	90° Adhesion to Steel (oz/in of width)	41 (11.2 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	3 (0.8 N/25mm)
	To Steel	24 (6.6 N/25mm)
	Tensile Strength (lbs/in of width)	131 (574 N/25mm)
	Elongation (% at break)	3
	Thickness (mils)	4.9 (0.124 mm)

Features: Temperature Resistant operating range of 40° F to 225° F. (4°C to 93°C)

Standard Sizes: 9mm x 54.8m, 12mm x 54.8m, 15mm x 54.8m, 18mm x 54.8m, 24mm x 54.8m, 36mm x 54.8m, 48mm x 54.8m, 72mm x 54.8m

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

07/03