



intertape polymer group

Product Code **RG-300**

**Product:** **RG-300 – Utility Grade / Uni-Directional Fiberglass Reinforced Tape**

**Description:** RG-300 is an economical fiberglass reinforced tape designed for the majority of packaging, palletizing and unitizing applications. The one mil polypropylene film combined with an aggressive ‘solventless’ pressure-sensitive adhesive provides excellent adhesion to corrugated cartons and outstanding holding power.

<b>Nominal Values:</b>	Backing	1.0 Mil (25 $\mu$ ) Biaxially Oriented Polypropylene Film
	Adhesive	Synthetic Rubber/Resin
	Color	Clear , White
	Reinforcement	Fiberglass
	Adhesion to Steel (oz/in of width) (at 90 degrees peel angle)	48 (13 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	8 (2.2 N/25mm)
	To Steel	30 (8.2 N/25mm)
	Tensile Strength (lbs/in of width)	100 (438 N/25mm)
	Elongation (% at break)	3
	Thickness (mils)	4.0 (0.102 mm)
	Shear to Kraft Paper (hrs) (1” x 1” x 1000 grams)	Greater than 96

**Standard Sizes:** 9mm x 54.8m, 12mm x 54.8m, 18mm x 54.8m, 24mm x 54.8m, 48mm x 54.8m, 72mm x 54.8m

**NOTICE:** While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

12/06

3647 Cortez Road West, Suite 102 • Bradenton, Florida, U.S.A. 34210

©Copyright, 1999 Intertape Polymer Group

PRODUCT DATA SHEET